

MATERIAL SAFETY 3M  
DATA SHEET 3M Center  
St. Paul, Minnesota  
55144-1000  
1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company.  
All rights reserved. Copying and/or downloading of this  
information for the purpose of properly utilizing 3M products  
is allowed provided that:

- 1) the information is copied in full with no changes unless  
prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise  
distributed with the intention of earning a profit thereon.

DIVISION: COMMERCIAL CARE DIVISION

TRADE NAME:

3M Brand NEUTRAL FLOOR CLEANER, SPANGLE Brand NEUTRAL FLOOR CLEANER  
ID NUMBER/U.P.C.:

61-5000-3762-9 00-48011-08780-6 61-5000-3763-7 00-48011-08781-8  
70-0708-3666-6 00-48011-23806-2

ISSUED: April 17, 2001

SUPERSEDES: June 02, 1998

DOCUMENT: 10-9285-7

1. INGREDIENT	C.A.S. NO.	PERCENT
WATER.....	7732-18-5	60 - 90
ETHOXYLATED PROPOXYLATED SECONDARY ALCOHOLS.....	68551-14-4	3 - 7
2-BUTOXYETHANOL.....	111-76-2	3 - 7
ACRYLIC ACID, POLYMERS.....	9003-01-4	1 - 5
TETRASODIUM ETHYLENEDIAMINETETRAACETATE.	64-02-8	1 - 5
PHOSPHATE ESTER POTASSIUM SALT.....	TradeSecret	1 - 5
SODIUM XYLENE SULFONATE.....	1300-72-7	1 - 5
SODIUM HYDROXIDE.....	1310-73-2	< 1

IN CASE OF EMERGENCY: THE NUMBERS AT THE TOP OF THIS PAGE PROVIDE 24  
HOUR RESPONSE FROM ANY PHONE FOR ALL EMERGENCIES WITH THIS PRODUCT.

This product contains the following toxic chemical or chemicals subject to  
the reporting requirements of Section 313 of Title III of the Emergency  
Planning and Community Right-To-Know Act of 1986 and 40 CFR Part 372:

2-BUTOXYETHANOL

## 2. PHYSICAL DATA

BOILING POINT:..... 212 F  
VAPOR PRESSURE:..... N/D  
VAPOR DENSITY:..... N/D  
EVAPORATION RATE:..... N/D  
SOLUBILITY IN WATER:..... complete  
SPECIFIC GRAVITY:..... ca. 1 Water=1

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
2. PHYSICAL DATA (continued)  
-----

PERCENT VOLATILE:..... ca. 80 %  
pH:..... ca. 9.8  
VISCOSITY:..... < 100 centipoise  
MELTING POINT:..... N/A

APPEARANCE AND ODOR:

Liquid, clear; light blue color; mild citrus fragrance

-----  
3. FIRE AND EXPLOSION HAZARD DATA  
-----

FLASH POINT:..... N/A  
FLAMMABLE LIMITS - LEL:..... N/A  
FLAMMABLE LIMITS - UEL:..... N/A  
AUTOIGNITION TEMPERATURE:..... N/D

EXTINGUISHING MEDIA:

Water, Carbon dioxide, Dry chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained,  
positive pressure or pressure demand breathing apparatus, bunker coat  
and pants, bands around arms, waist and legs, face mask, and  
protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

No unusual fire or explosion hazards are anticipated.

NFPA HAZARD CODES: HEALTH: 1 FIRE: 1 REACTIVITY: 0

UNUSUAL REACTION HAZARD: none

-----  
4. REACTIVITY DATA  
-----

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

Not applicable.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Oxides of Nitrogen, Oxides of  
Sulfur, Hydrocarbons.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
5. ENVIRONMENTAL INFORMATION  
-----

SPILL RESPONSE:

Observe precautions from other sections. Ventilate area. Cover with absorbent material. Collect spilled material. Clean up residue with water. Place in an approved metal container. Seal the container.

RECOMMENDED DISPOSAL:

Flush spent solutions and small quantities (less than 5 gal.(19 L)) to a wastewater treatment system. Reduce discharge rate if foaming occurs. Dispose of empty cans in a sanitary landfill. For larger quantities: Incinerate in an industrial or commercial facility in the presence of a combustible material.

ENVIRONMENTAL DATA:

Not determined.

REGULATORY INFORMATION:

Volatile Organic Compounds: ca. 50 gms/liter South Coast Air Quality Mgmt Dist Method Rule 443.1, calculated.  
VOC Less H<sub>2</sub>O & Exempt Solvents: ca. 50 gms/liter South Coast Air Quality Mgmt Dist Method Rule 443.1, calculated.

Since regulations vary, consult applicable regulations or authorities before disposal. U.S. EPA Hazardous Waste Number = None (Not U.S. EPA Hazardous).

TSCA: All chemicals used in the manufacture of this material are listed on the US TSCA inventory.

EPCRA HAZARD CLASS:

FIRE HAZARD: No PRESSURE: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

-----  
6. SUGGESTED FIRST AID  
-----

EYE CONTACT:

Immediately flush eyes with large amounts of water. Get immediate medical attention.

SKIN CONTACT:

Flush skin with large amounts of water. If irritation persists, get medical attention.

INHALATION:

Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, get immediate medical attention.

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
6. SUGGESTED FIRST AID (continued)  
-----

IF SWALLOWED:

Do not induce vomiting. Drink two glasses of water. Call a physician.

-----  
7. PRECAUTIONARY INFORMATION  
-----

EYE PROTECTION:

Avoid eye contact. Wear vented goggles.

SKIN PROTECTION:

Avoid skin contact. Wear appropriate gloves when handling this material. A pair of gloves made from the following material(s) are recommended: butyl rubber.

RECOMMENDED VENTILATION:

Use in a well-ventilated area. Use with adequate dilution ventilation.

RESPIRATORY PROTECTION:

Avoid breathing of vapors.

PREVENTION OF ACCIDENTAL INGESTION:

Do not ingest.

RECOMMENDED STORAGE:

Keep container closed when not in use. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Keep container tightly closed.

HMIS HAZARD RATINGS: HEALTH: 0 FLAMMABILITY: 0 REACTIVITY: 0  
PERSONAL PROTECTION: X (See precautions, section 7.)

EXPOSURE LIMITS

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
WATER.....	NONE	NONE	NONE	NONE	
ETHOXYLATED PROPOXYLATED SECONDARY ALCOHOLS.....	NONE	NONE	NONE	NONE	
2-BUTOXYETHANOL.....	25	PPM	TWA	ACGIH	Y
2-BUTOXYETHANOL.....	25	PPM	TWA	OSHA	Y
	OSHA VACATED PEL				
2-BUTOXYETHANOL.....	50	PPM	TWA	OSHA	Y
ACRYLIC ACID, POLYMERS.....	NONE	NONE	NONE	NONE	
TETRASODIUM ETHYLENEDIAMINETETRAACETATE.....	NONE	NONE	NONE	NONE	
PHOSPHATE ESTER POTASSIUM SALT.....	NONE	NONE	NONE	NONE	

-----  
Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

EXPOSURE LIMITS (continued)

INGREDIENT	VALUE	UNIT	TYPE	AUTH	SKIN*
SODIUM XYLENE SULFONATE.....	NONE	NONE	NONE	NONE	
SODIUM HYDROXIDE.....	2	MG/M3	CEIL	ACGIH	
SODIUM HYDROXIDE.....	2	MG/M3	CEIL	OSHA	
SODIUM HYDROXIDE.....	2	MG/M3	TWA	CMRG	
	15 MINUTES TWA				

\* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- ACGIH: American Conference of Governmental Industrial Hygienists
- CMRG: Chemical Manufacturer Recommended Exposure Guidelines
- OSHA: Occupational Safety and Health Administration
- OSHAV: Occupational Safety and Health Administration Vacated PEL. Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory authority.

- NONE: None Established

8. HEALTH HAZARD DATA

EYE CONTACT:

Mild Eye Irritation: signs/symptoms can include redness, swelling, pain, and tearing.

SKIN CONTACT:

Mild Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, and itching.

May be absorbed through the skin and produce effects similar to those caused by inhalation and/or ingestion.

INHALATION:

Single overexposure, above recommended guidelines, may cause:

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD,

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

-----  
8. HEALTH HAZARD DATA (continued)  
-----

THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Prolonged or repeated overexposure, above recommended guidelines, may cause:

Kidney Effects: signs/symptoms can include reduced urine volume, blood in urine and back pain.

Liver Effects: signs/symptoms can include yellow skin(jaundice) and tenderness of upper abdomen.

IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

Ingestion may cause:

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

Aspiration Pneumonitis: signs/symptoms can include coughing, difficulty breathing, wheezing, coughing up blood and pneumonia, which can be fatal.

-----  
SECTION CHANGE DATES  
-----

PRECAUTIONARY INFO. SECTION CHANGED SINCE June 02, 1998      ISSUE

-----  
Abbreviations: N/D - Not Determined   N/A - Not Applicable   CA - Approximately  
-----

-----

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.